



SMOKE ALARMS

Data Sheet



Mini-968/10Y

Carbon Monoxide Alarm, Photoelectric, 3V Sealed Battery

Key Information

| | |
|-------------------------|--|
| Product brand: | Red Smoke Alarms |
| Product or component: | Carbon Monoxide Detector |
| Device application: | Early detection of carbon monoxide leakage |
| Electronic sensor type: | Electrochemical sensor |
| Colour: | White (RAL 9003) |
| Quantity per set: | Set of 1 |
| Type of packing: | Carton |

Complementary

| | |
|----------------------|--|
| Supply | 3V DC Sealed Battery |
| Battery Type | Lithium Battery |
| Battery Life | 10 Year |
| Operating Current | ≤150mA at 3V |
| Standby Power | ≤10mA |
| Detection Type | Carbon Monoxide |
| Function Available | Hush Function Self-test of CO detection Local alarm |
| Control Type | Button for test/ hush function |
| Alarm Response Time | 50 PPM (60-90 mins) 100 PPM (10-40 mins) 300 PPM (<3 mins) |
| Noise Level | 85 dB at 3m minimum |
| Time Delay Range | 10 min for hush 10 hr for do not disturb |
| Local Signal | Sound : Alarm Sound : Signal Power Activation Signal (Green Light) Fault Warning (Yellow light flash 2 times) End of Life Signal (Yellow light flash 3 times) CO gas Warning Signal (Red Light) |
| Type of Installation | Indoor |
| Device Mounting | Surface |
| Mounting Support | Wall-mount |
| Fixing Mode | By screws |
| Dimension: | 90 x 22 x 90 mm (L x W x H) |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.

Neither Red Smoke Alarms PTY. LTD nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

| | |
|---------------------------------------|--|
| Ambient Air Temperature for Operation | 0...50°C |
| Relative Humidity | 5...95% |
| Standards | EN50291-1:2012+A1:2010 Intertek Certificate No. 22302 |



Data Sheet
Mini-968/10Y

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability of reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.

Neither Red Smoke Alarms PTY. LTD nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.