

Vactron CVX925 Ducted Vacuum System (Hybrid-Bag or Bagless)

| INSTALLATION RECOMMENDATIONS | |
|--|-----------------|
| Size of Building up to Squares | 40 |
| Number of Inlet Points | 4 |
| Working Hose length – | up to metres 15 |
| Hide-A-Hose Compatible: | No |
| MOTOR SPECIFICATIONS | |
| Peripheral By-pass discharge- | Yes |
| Turbine Stages- | 2 |
| Double ball bearings- | Yes |
| Diameter of Motor mm- | 145 |
| Air Watts- | 660 |
| Airflow I/s (max.)- | 57 |
| Sealed Vacuum mm H2O- | 3350 |
| RPM (max) | 30200 |
| Label Rated Electrical Watts- | 1800 |
| Control Circuit 12 V DC- | Yes |
| Control Current 100mA- | Yes |
| Nominal Voltage 240V AC- | Yes |
| POWER UNIT PHYSICAL SPECIFICATIONS | |
| Overall Height (mm) | 1000 |
| Overall Diameter (mm) | 410 |
| Hybrid Tri Flow Filiation Compatible System- | Yes |
| Cyclonic Filtration with Hepa Filter- | Yes |
| Silencer for Exhaust- | Yes |
| Left & Right ducting entry points- | Yes |
| Dirt Canister port view- | Yes |
| Dirt Canister liters- | 25 |
| Wall Mounting of Power Unit- | Yes |
| AUTHORITY/ APPROVAL/ ORIGIN | |
| "C" Tick Compliance EMC – | AS/NZS 1044 |













FEATURE

- 1800W Commercial grade peripheral discharge motor
- High-capacity dirt canister with quick release latches- only needs to be emptied a few times each year
- On-board garage/utility valve with on/ off switch allows convenient cleaning directly from the vacuum.
- 2 Inlet openings one on the let and one on the right - this allows you to mount the unit in almost any space and connect your existing pipe to the unit easily
- Hybrid Tri Flow Filtration System for 3 Cleaning options (Bag, Bagless, Self-Cleaning)
- Wall-mount bracket for simple, safe and secure mounting
- An integrated silencer is included which connects to the exhaust vent of the motor - this reduces the air flow noise down which allows for a more comfortable operation inside your home.
- True HEPA filtration
- 2 Year EVS Warranty