



EP-FFG2-D32



EP-FFG2-D63

FIREFLY SERIES EMERGENCY CEILING

The Firefly Emergency Light is easy to install and supported by a premium, 2-hour backup Lithium Nanophosphate (LiFePO4) battery.

They are fully compliant to the AS/NZS 60598.2.22:2019 emergency lighting standard.

FEATURES - D32 AND D63

- 3 year Lithium BST LiFePO4 battery 1.8W LED
- EP-FFG2-D32: 1.3W
- EP-FFG2-D63: 2.5W
- Non-maintained mode
- 2hr emergency power
- EP-FFG2-D32: 3.2V, 1500mAh
- EP-FFG2-D63: 6.4V, 1500mAh
- 75mm-130mm cut-out

SPECIFICATIONS

WARRANTY	3 Years	MODEL NUMBER	POWER	MODE	BATTERY	EMERGENCY	CLASSIFICATION
		EP-FFG2-D32	1.3W	Non-maintained	LiFePO4,1500mAH	2 hours	C0:D32 C90:D32
		EP-FFG2-D63	2.5W	Non-maintained	LiFePO4,1500mAH	2 hours	C0:D63 C90:D63

FIREFLY SURFACE MOUNT KIT

- Suited for Emerald Planet Firefly Series Emergency Light
- Can be surface mounted or suspended
- 75mm cut-out lighting standard.

SPECIFICATIONS

MODEL NUMBER	DIMENSIONS
EP-FFG2-SM	75mm cut out



Firefly Surface Mount Kit