




DA035 CTD

CCT ADJUSTABLE CEILING LIGHT

DA035 CTD is a light-weight, simplistic LED down light with a beam angle of 90°, suitable for domestic and light commercial applications. But that is just the beginning; beneath the hood lies the real power of this dynamic little luminaire - adjustable colour temperature from 3000 K to 5000 K. No more will designers and installers have to juggle multiple models for various locations on site - with the DA035 CTD, selecting colour temperature is as easy as flicking a switch.* Additional benefits include the simplification of purchasing, picking and packing, storage, and the peace of mind that comes from the removal of one more hassle.

DA035 CTD offers an integrated driver and fully retractable spring clips, and provides a soft, tender light that will enhance a wide variety of installation environments.

(* CCT selection is made prior to installation)



FEATURES

- » Enhanced performance
- » 10 W output
- » Integrated LED dimmable driver
- » High performance LEDs, up to 40,000 hr
- » CCT selectable: 3000 K - 5000 K
- » IP44 below ceiling, IP20 above
- » IC-4 insulation rating
- » Dimmable
- » 0.75 m supply flex & 2-pin plug
- » Quick and easy installation

APPLICATIONS

- » Retail shops
- » Bars, restaurants
- » Galleries
- » Display areas
- » Bedrooms, lounge rooms

SPECIFICATIONS

Model	DA03510WCTD01		
Power	10 W		
Supply Voltage	200 - 240 VAC, 50 / 60 Hz		
CCT	3000 K	4000 K	5000 K
Lumen Output	865 lm	1034 lm	984 lm
Efficacy	87 lm/W	103 lm/W	98 lm/W
Power Factor	> 0.9		
CRI	> 80		
Beam Angle	90°		
Dimmable	yes		
LED Lifetime	40,000 hrs		
Ta (max.)	40° C		

Manufactured under ISO 9001:2008 to standards

AS/NZS60598.1
AS/NZS60598.2.1
AS/NZS60598.2.2



AS/NZS CISPR 15



DA035CTD 170824


LIGHTING DATA

DA03510WCTD01 3000K



Utilisation Table (TM5)				DA03510WCTD.IES									
Reflectances			Room Index										
C	W	F	0.75	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0		
70	50	20	54	63	70	75	82	87	90	95	98		
70	30	20	46	56	63	68	76	81	85	91	94		
70	10	20	40	50	57	63	71	77	81	87	91		
50	50	20	51	60	66	71	77	82	85	89	91		
50	30	20	44	53	60	65	72	77	80	85	88		
50	10	20	39	48	55	60	68	73	77	82	86		
30	50	20	48	57	62	67	73	77	79	83	85		
30	30	20	42	51	57	62	68	73	76	80	83		
30	10	20	38	47	53	58	65	70	73	78	81		
0	0	0	35	43	49	53	59	64	67	71	74		
BZ-class			5	5	5	5	5	5	5	5	5		
SHRnom : 1.25						SHRmax : 1.387							


CCT ADJUSTMENT



Use the slide switch to select the required CCT

- N = 4000 K
- C = 5000 K
- W = 3000 K

DIMENSIONS



Characteristics and specifications may change without notice. All electrical installations / connections should be carried out by a competent person at all times. Application images are indicative only and may not contain actual Davis product. The information contained in this publication is typical and must not be interpreted as a guarantee of individual product performance.

AUSTRALIA

HEAD OFFICE: Tel: +61 (7) 3712 8988 Fax: +61 (7) 3272 8988
SALES OFFICES (all states): 1300 851 001

E-mail: australia@davislighting.com
Website: www.davislighting.com