

PAN PNB CT

Commercial Lighting / Backlit Panel Light

PNBW230CT (5000K)



DAVISLIGHTING



Features

- Switchable colour temperature
- Uniform light effect
- Integrated steel plate design provides excellent thermal management
- Concise design offers high performance
- Remote driver
- Various mounting methods
- Available in dimming version

Applications

- Offices / meeting rooms
- Schools
- Hospitals
- Laboratory / Dust-free workshop


Options

- Surface Mount Kit
- Plaster Frame Kit
- Suspension Kit

Standards

- Manufactured under ISO 9001:2015 to standards
- IEC/AS/NZS 60598.1
- IEC/AS/NZS 60598.2.2
- IEC/AS/NZS CISPR 15

Mounting Methods



T-Bar Lay-in

Plaster Recessed



Surface mounted

Suspension



PAN PNB CT

Commercial Lighting / Backlit Panel Light

Specifications

Model	PNBW230CT (5000K)
Nominal Power (W)	30
Input Voltage (V)	200-240
Frequency (Hz)	50/60
Luminaire Flux (lm)	3734
Luminaire Efficacy (lm/W)	124
CRI (Ra)	>80
Power Factor	>0.90
SDCM	<5
CCT (K)	5000
Luminaire Rated Life (hr)	50000
Operating Temp. (°C)	-20 to +40
Weight (kg)	2.5
IP Rating	40


Packaging Details

Model	PNBW230CT (5000K)
Product Carton Qty per box (pc)	1
Product Carton Dimension (mm)	599 x 52 x 616
Product Carton Weight (kg)	2.16
Master Carton Qty per box (pc)	6
Master Carton Dimension (mm)	608 x 331 x 635
Master Carton Weight (kg)	12.94

PAN PNB CT

Commercial Lighting / Backlit Panel Light

Lighting Data



Dimensions

